



# 6500, 2100 series Fixed Casement WINDOW PERFORMANCE TABLE



Model	Style	VT	Metric U-Factor W/m <sup>2</sup> .k	Imperial U-Factor Btu/h ft <sup>2</sup> F	Imperial Value R	SHGC	ER	Canada (Yes/No)	US Zones	NAF TEST RESULTS MAXIMUM SIZE TESTED
<b>6500/2100 Series Fixed Casement</b>										
6520CLEAR	Fixed Casement	0.59	2.33	0.41	2.44	0.56	21			CW-PG55-C, Size Tested (32 x 59)
6520_4MM_CLEAR	Fixed Casement	0.59	2.33	0.41	2.44	0.55	20			CW-PG55-C, Size Tested (32 x 59)
6520CLEAR_GRIDS	Fixed Casement	0.54	2.33	0.41	2.44	0.51	18			CW-PG55-C, Size Tested (32 x 59)
6520_4MM_CLEAR_GRIDS	Fixed Casement	0.53	2.33	0.41	2.44	0.5	18			CW-PG55-C, Size Tested (32 x 59)
6520SOLR_GAIN	Fixed Casement	0.57	1.59	0.28	3.57	0.51	34	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_SOLR_GAIN	Fixed Casement	0.57	1.59	0.28	3.57	0.5	34	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520FROSTED_SOLR_GAIN	Fixed Casement	0.57	1.59	0.28	3.57	0.51	34	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520FROSTED_4MM_SOLR_GAIN	Fixed Casement	0.57	1.59	0.28	3.57	0.5	34	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520SOLR_GAIN_GRIDS	Fixed Casement	0.52	1.59	0.28	3.57	0.47	32		N	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_SOLR_GAIN_GRIDS	Fixed Casement	0.51	1.59	0.28	3.57	0.45	31		N	CW-PG55-C, Size Tested (32 x 59)
6520FROSTED_SOLR_GAIN_GRIDS	Fixed Casement	0.52	1.59	0.28	3.57	0.47	32		N	CW-PG55-C, Size Tested (32 x 59)
6520FROSTED_4MM_SOLR_GAIN_GRIDS	Fixed Casement	0.51	1.59	0.28	3.57	0.45	31		N	CW-PG55-C, Size Tested (32 x 59)
6520EVOLV	Fixed Casement	0.56	1.36	0.24	4.17	0.47	37	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_EVOLV	Fixed Casement	0.55	1.36	0.24	4.17	0.45	36	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520EVOLV_GRIDS	Fixed Casement	0.51	1.36	0.24	4.17	0.43	35	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_EVOLV_GRIDS	Fixed Casement	0.5	1.36	0.24	4.17	0.41	34	Y	N	CW-PG55-C, Size Tested (32 x 59)
6520SOLR_SHIELD_PLUS_366	Fixed Casement	0.47	1.48	0.26	3.85	0.29	24		N, NC	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_SOLR_SHIELD_PLUS_366	Fixed Casement	0.46	1.48	0.26	3.85	0.28	24		N, NC	CW-PG55-C, Size Tested (32 x 59)
6520SOLR_SHIELD_PLUS_366_GRIDS	Fixed Casement	0.42	1.48	0.26	3.85	0.26	22		N, NC	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_SOLR_SHIELD_PLUS_366_GRIDS	Fixed Casement	0.42	1.48	0.26	3.85	0.26	22		N, NC	CW-PG55-C, Size Tested (32 x 59)
6520EVOLV_366_LOWE	Fixed Casement	0.45	1.31	0.23	4.35	0.2	23		N, NC, SC, S	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_EVOLV_366_LOWE	Fixed Casement	0.45	1.31	0.23	4.35	0.2	23		N, NC, SC, S	CW-PG55-C, Size Tested (32 x 59)
6520EVOLV_366_LOWE_GRIDS	Fixed Casement	0.41	1.31	0.23	4.35	0.18	21		N, NC, SC, S	CW-PG55-C, Size Tested (32 x 59)
6520_4MM_EVOLV_366_LOWE_GRIDS	Fixed Casement	0.41	1.31	0.23	4.35	0.18	21		N, NC, SC, S	CW-PG55-C, Size Tested (32 x 59)